


WEAVED SCREEN FABRIC WITH VARIED OPENNESS
FACTORS TO REDUCE GLARE AND MANAGE DAYLIGHT

SPECIFICATION


BLIND TYPE	ROLLER
FUNCTION	SCREEN
OPENNESS FACTOR	3%
CLEANING	WASHABLE
WEIGHT	470 G/M2 APPROX
FIRE RETARDANCY	C1
COMPOSITION	70% PVC / 30% POLYESTER
WIDTH	2000MM, 2500MM AND 3000MM




COLOURS




Clarity




Beach



Dawn



Oakmoss



Wire



Graphite

TECHNICAL INFORMATION

COLOUR	HEAT			LIGHT		
	T	R	A	T	R	A
Clarity	24	63	13	21	73	6.5
Beach	23	58	19	18	66	15
Dawn	16	42	42	12	47	41
Wire	9.1	32	59	4.1	33	63
Graphite	3.2	2.9	94	3.2	2.8	94
Oakmoss	3.7	9.9	86	3.4	11	86

T% : Transmittance

R% : Reflectance

A% : Absorption

THICKNESS: 0.58 MM

OPENNESS FACTOR: 3%

COLOUR FASTNESS: 4.5

UV SCREEN: 97%

TENSILE STRENGTH WARP: 30%

TENSILE STRENGTH WEFT: 20%

TEAR STRENGTH WARP: 14.5 DAN

TEAR STRENGTH WEFT: 15 DAN